

INSTALLATION INSTRUCTIONS FOR  
**VS300 series**  
**AUTO BUG SCREEN**



By



Thank you for purchasing one of our fine quality products. Your bug screen is engineered from high quality materials and designed with precision to give you long-lasting, trouble-free usage. Enclosed are: - one bug screen - two hooks - four shock cords

**INSTALLATION:**

1. Tie knot at one end of each cord
2. Pass the unknotted ends through each of the bottom eyelets
3. Continue to feed each cord through each hook and continue to top eyelet
4. Knot the cord at the top eyelet but do not tighten
5. Center the bug screen on your vehicle and secure hooks inside the wheel well
6. Pull the shock cord to tighten firmly and adjust knot in place
7. On some vehicles the middle eyelet with shock cord may be required.
8. See diagrams below



**IMPORTANT:** Install until tight enough to avoid any movement while driving. On some cars it may be necessary to secure the top of the screen under the hood to prevent flapping at highway speeds.

**CAUTION:** Hold "S" hooks firmly when installing bug screen in order to keep hooks from springing loose.



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438  
Fax: (204) 284-8246 E-Mail: [infofia@mb.sympatico.ca](mailto:infofia@mb.sympatico.ca) Website: [www.gofia.com](http://www.gofia.com)

INSTALLATION INSTRUCTIONS FOR  
**VS300 series**  
**AUTO BUG SCREEN**


By



Thank you for purchasing one of our fine quality products. Your bug screen is engineered from high quality materials and designed with precision to give you long-lasting, trouble-free usage. Enclosed are: - one bug screen - two hooks - four shock cords

**INSTALLATION:**

1. Tie knot at one end of each cord
2. Pass the unknotted ends through each of the bottom eyelets
3. Continue to feed each cord through each hook and continue to top eyelet
4. Knot the cord at the top eyelet but do not tighten
5. Center the bug screen on your vehicle and secure hooks inside the wheel well
6. Pull the shock cord to tighten firmly and adjust knot in place
7. On some vehicles the middle eyelet with shock cord may be required.
8. See diagrams below:



**IMPORTANT:** Install until tight enough to avoid any movement while driving. On some cars it may be necessary to secure the top of the screen under the hood to prevent flapping at highway speeds.

**CAUTION:** Hold "S" hooks firmly when installing bug screen in order to keep hooks from springing loose.



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-043  
Fax: (204) 284-8246 E-Mail: [info@gofia.com](mailto:info@gofia.com) Website: [www.gofia.com](http://www.gofia.com)